



KEY: THICKNESS:		
1	3 1/2"	2.5" MIN. STRUCTURAL COURSE IN 2 LIFTS (SP 9.5) PER FDOT SPECIFICATIONS
		1" MIN. FRICTION COURSE (FC 9.5) PER FDOT SPECIFICATIONS
2	10"	LIMEROCK IN 2 LIFTS - 98% COMPACTION EACH LIFT, A.A.S.H.T.O. T-180, PRIMED & SANDED. (LBR 100)
3	12"	TYPE B STABILIZED SUBGRADE LBR 40, 98% COMPACTION, A.A.S.H.T.O. T-180.

NOTE:

1. ALL STRIPING TO BE LEAD & SOLVENT FREE THERMOPLASTIC IN ACCORDANCE WITH FDOT SPECIFICATION 711 UNLESS OTHERWISE NOTED.
2. SOD ALL DISTURBED AREAS.
3. MAXIMUM DESIGN SPEED IS 45 MPH.
4. FOR SUPERPAVE UTILIZE TRAFFIC LEVEL C.

ARTERIAL ROAD - MULTILANE

STANDARD PAVING SECTION

SCALE: N.T.S.



LEESBURG
The Lakefront City

City of Leesburg
Standard Details

2024

DETAIL ST- 4